

[The durafoot® FX]

The durafoot®FX range of mounting blocks offers a simple and economical solution for securing and carrying cable tray, pipework and ducting without the need for a framing system.



[Technical Specification]

Supplier's Part Number	Product	Length (mm)	Height (mm)	Width (mm)	Max Load Bearing per Foot (kg)	Ballast Weight per Foot (kg)
2103400	durafoot® FX 250 + Pre-Galv Channel	250	95	180	160	2.7
2103420	durafoot® FX 400 + Pre-Galv Channel	400	95	180	400	4.2
2103460	durafoot® FX 600 + Pre-Galv Channel	600	95	180	450	6.3
2103480	durafoot® FX 1000 + Pre-Galv Channel	1000	95	180	645	10.5
2103900	durafoot® FX 250 low + Pre-Galv Channel	250	50	130	160	1.3
2103920	durafoot® FX 400 low + Pre-Galv Channel	400	50	130	400	2.6

[Material Specification]

Foot - SBR (Styrene Butadiene Rubber), recycled, with a Polyurethane Pre-Polymer, moisture curing bond.
UV stabilised
Environmentally friendly

Channel - Pre-Galvanised Steel
Cold rolled to BS EN 10149-3
Pre-Galvanised to BS EN 10147:1992 (coating Z275)

[Working Conditions]

Temperature tolerance	Indoor use	Outdoor use
-40°C to +80°C	✓	✓